


MODEL KMW1020
10 WATTS CW
500 kHz - 512 MHz

The Model KMW1020 is an RF power amplifier module for OEM applications or integration into a user system. The module comprises a printed wiring assembly housed in a machined aluminum enclosure with feed-through capacitive terminals for connection to the DC power source. Cooling requirements defined by the data provided below and protection of the output devices against output mismatch are the responsibility of the user.

SPECIFICATIONS

RATED POWER OUTPUT	10 Watts
INPUT FOR RATED OUTPUT	1.0 mW maximum
POWER OUTPUT @ 1db COMPRESSION	11 Watts minimum
CLASS OF OPERATION.....	Class AB
FLATNESS	± 1.5 dB maximum
FREQUENCY RESPONSE.....	500 kHz - 512 MHz
GAIN	40 dB minimum
INPUT IMPEDANCE.....	50 Ohm nominal, VSWR 2:1 maximum
OUTPUT IMPEDANCE	50 Ohm nominal
MISMATCH TOLERANCE	2:1 maximum
MODULATION CAPABILITY.....	Will faithfully reproduce AM, FM, or pulse modulation appearing on the input signal
NOISE FIGURE (above 1.0 MHz)	10 dB typical
HARMONIC DISTORTION	- 20 dBc maximum
PRIMARY POWER	24 V @ 3.2 A (Solder terminals)
RF CONNECTORS	SMA female
COOLING.....	Maximum allowable enclosure temperature 60 °C



MODEL CONFIGURATIONS

MODEL NUMBER	HEATSINK	HEATSINK SPECS	WEIGHT	SIZE (WxHxD)
KMW1020	NO	-	0.82 kg (1.8 lb.)	9.52 x 3.36 x 17.78 cm 3.75 x 1.32 x 7.0 in.
KMW1020M1	YES	.68 kg, 27.8 sq.in/1", 2.5 °C/W/3"	1.5 kg (3.3 lb.)	9.52 x 6.54 x 17.78 cm 3.75 x 2.58 x 7.0 in

