



MODEL AR-20B (BKT & BKT-DUAL)
20 WATTS CW/PEP
30-512 MHz

The Model AR-20B is a portable, lightweight, fully automatic band-switching RF booster amplifier for use with multi-band VHF/UHF Tactical Radio equipment employing legacy, proprietary and networking waveforms. The AR-20B produces 20 Watts and covers the frequency band of 30-512 MHz. The unit has a wide range input DC voltage allowing operation from a single battery (XX90 battery) or 12 and 28 VDC vehicle power sources.

It also includes Over Temperature Protection, RF sensing, T/R Switching, Automatic Level Control (ALC), Harmonic Filters, Co-Site filters and protection against antenna mismatch. The amplifier is comprised of a rugged 4-piece aluminum case. The AR-20B is the simpler version of the 20W family without an LNA and power select (contact AR Modular RF for the unit with the LNA feature). Optional interface coaxial cables, DC battery cables, and kits for man-packing the amplifier are available.

GENERAL SPECIFICATIONS

| | |
|------------------------|--|
| FREQUENCY RANGE | 30-512 MHz |
| POWER OUTPUT | 20 Watts CW or PEP AM Modulation 1 kHz DOM 70%; <10% AM distortion nominal |
| INPUT POWER RANGE | Nominal 2W CW or PEP for 20W output. Up to 8W without damage |
| RF KEYING SENSITIVITY | <1 Watt CW typical |
| T/R SWITCHOVER TIME | <25 μS |
| MODULATION | Compatible and tested with legacy & modern complex waveforms including AM, FM, HPW, DAMA, IW, ANW2 and SRW |
| DUTY CYCLE | Tactical operations 100% for networking modulations |
| INPUT/OUTPUT IMPEDANCE | 50 Ohm nominal |
| INPUT VSWR | 1.5:1 nominal |
| HARMONICS | Better than -60 dBc typical |
| SPURIOUS OUTPUTS | Better than -70 dBc |
| POWER REQUIREMENT | 12 to 35.5 VDC single XX90 battery, 12 and 28Vdc vehicles |
| CURRENT | 3.2A Amps @ 24V typical |

ENVIRONMENTAL SPECIFICATIONS

| | |
|---------------------------------------|---|
| OPERATING TEMPERATURE | -30 to +60 °C Ambient |
| ALTITUDE (operating) | 15,000 ft |
| IMMERSION (water) | IP67 |
| VIBRATION / SHOCK / HUMIDITY / ENVIRO | Designed to meet applicable sections of Mil Std 810F/Designed for ground/base vehicle use |

MECHANICAL SPECIFICATIONS

| | |
|---------------|---|
| SIZE (HxWxD) | 1.58 x 3.75 x 5.05 inches |
| WEIGHT | AR-20B: 1 lb 10 oz AR-20BKT: 2 lbs 15 oz AR-20BKT-DUAL: 4 lbs 5 oz |
| COOLING | Natural convection required |
| RF CONNECTORS | RF Input(Radio) – TNC* RF Output(antenna) – TNC * <i>*RF connectors may be ordered in any configuration of TNC or N-type per customer's request</i> |
| DC CONNECTOR | Multi-pin connector (Mating Connector is included) |
| CONSTRUCTION | Aluminum housing with integral heatsink |

modular rf

OPTIONAL EQUIPMENT & ACCESSORIES

| ARM Model Name | Description |
|----------------|-------------------------------|
| MP-AR-20-01 | Mounting plate – length mount |
| MP-AR-20-02 | Mounting plate – width mount |

Speak with your AR Modular RF sales representative for additional accessories including power pig tails and other items.



(AR-20B 20W amp only without LNA)

modular rf

AR-20BKT

| | |
|--------|--|
| AR-20B | 20 Watts, 30-512 MHz RF Booster Amplifier |
| BC20 | Battery Cable (22" cable connecting AR-20B to one XX90 or similar batteries) |
| RC20 | Radio Cable (36" TNC Male to TNC Male) |
| AC20 | Antenna Cable (36" TNC Male to TNC Female) |
| TVP20 | Tactical Vest Pouch (Attaches to any MOLLIE/PALS style gear for holding the AR-20) |
| ANT20 | Blade Antenna 30-512 MHz (TNC Male) |
| TAH20 | Tactical Antenna Holder (Attaches to any MOLLIE/PALS style gear for holding the ANT20) |



(AR-20BKT)

modular rf

AR-20BKT-DUAL

| | |
|---------------|--|
| AR-20B | 20 Watts, 30-512 MHz RF Booster Amplifier |
| BC20 | Battery Cable (22" cable connecting AR-20B to one XX90 or similar batteries) |
| RC20 | Radio Cable (36" TNC Male to TNC Male) |
| AC20 | Antenna Cable (36" TNC Male to TNC Female) |
| TVP20 | Tactical Vest Pouch (Attaches to any MOLLIE/PALS style gear for holding the AR-20) |
| TAH20 | Tactical Antenna Holder (Attaches to any MOLLIE/PALS style gear for holding the ANT20) |
| ANT20 | Blade Antenna 30-512 MHz (TNC Male) |
| RH-2535 | RamHead Tactical SATCOM Antenna and RF Cables |
| SSH1031 | SATCOM Switch Holder (Attaches to any MOLLIE/PALS style gear for holding the RFS-117) |
| LC20 | Antenna Blade (RF SW-LOS Blade Antenna STR BNC M-TNC F 36") |
| SC20 | BNC M to TNC M 36" SATCOM Antenna Cable |
| SATCOM SWITCH | RF Switch Kit – LOS/SATCOM w/TNC adapter |



(AR-20BKT-DUAL)

MODEL CONFIGURATIONS

| MODEL NUMBER | DESCRIPTION | WEIGHT |
|---------------|--|-------------|
| AR-20B | 20W Amp only | 1 lb 10 oz |
| AR-20BKT | 20W Amp with LOS antenna, cables, and pouches | 2 lbs 15 oz |
| AR-20BKT-DUAL | 20W Amp with LOS and SATCOM antennas, switch, cables and pouches | 4 lbs 5 oz |



ar modular rf

21222 30th Dr SE, Suite 200 • Bothell, Washington 98021 • 425-485-9000 • Fax 425-486-9657 www.arworld.us

DOC-00000266 REV D – 2022-03-03

Previously 7-98-940-910